

# DURADUCT<sup>®</sup>

## NUT WELDED CLAMPS



### Product Feature

- \* Electro Galvanised grooved steel body for strong grip on pipe.
- \* Welded Nut M8 + M10 for 1 / 2" to 4" and M10 + M12 for 5" to 6".
- \* Lock Bolt M6 - upto 4" and M8 - 5" onwards with PE washer to prevent Screw from falling.
- \* Twin thread Nuts for flexibility of fastening.
- \* EPDM Rubber lining or without Rubber lining.
- \* Can be used for Vertical as well as Horizontal installation.

### Features of Rubber Lining

- \* Suitable for temperature from 20 to 140 .
- \* Resistance against weather & ageing.
- \* Limited resistance against lubricating oil.
- \* Edge protection due to overlapping flaps.
- \* Provides sound insulation and thermal barrier.

ITEM CODE	NOMINAL PIPE SIZE		STRAP SIZE MM	LOCK BOLL SIZE MM	LOCKING SIZE MM
	INCHES	MM			
NWC 12	½"	20 - 24	20 X 1.6	6 X 20	8 / 10
NWC 34	¾"	26 - 30	20 X 1.6	6 X 20	8 / 10
NWC 100	1"	32 - 36	20 X 1.6	6 X 20	8 / 10
NWC 114	1 ¼"	38 - 42	20 X 1.6	6 X 20	8 / 10
NWC 112	1 ½"	46 - 50	20 X 1.6	6 X 20	8 / 10
NWC 200	2"	60 - 64	20 X 1.6	6 X 20	8 / 10
NWC 212	2 ½"	74 - 78	22 X 2.0	6 X 25	8 / 10
NWC 300	3"	86 - 90	22 X 2.0	6 X 25	8 / 10
NWC 400	4"	114 - 118	22 X 2.0	6 X 25	8 / 10
NWC 500	5"	138 - 142	25 X 2.5	8 X 25	10 / 12
NWC 600	6"	158 - 162	25 X 2.5	8 X 25	10 / 12

NOTE : \* RESEARCH & DEVELOPMENT IS A CONTINUOUS PROCESS WITH US. AS IMPROVEMENTS ARE MADE FROM TIME TO TIME, SPECIFICATIONS / DIMENSIONS MAY CHANGE WITHOUT NOTICE.  
\* TOLERANCES IN DIMENSIONS ARE AS PER INTERNATIONAL STANDARDS.



**RICHFIELD<sup>®</sup>**  
GROUP OF COMPANIES

205 / 206, Morya House, Veera Industrial Estate,  
Off New Link Road, Andheri (W), Mumbai 400 053. INDIA.  
Tel. : 91-22-2673 3171 / 2673 2947 Fax : + 91-22-2673 3147  
E-mail : abasrani@rediffmail.com